


Pro 1100 **mini**

**REALTIME**<sup>®</sup>  
*Power of Biometrics*

# Face Recognition

Access all employees attendance securely with High speed long range face recognition



Face Capacity  
**1500**



Card Capacity  
**1500**



PIN Capacity  
**1500**

**with WiFi**



# 4.0" HD Touch Screen



1500  
Face



1500  
Pin



1500  
Card



Access  
Control



TCP/IP



WiFi

With Free Cloud Software for Attendance and Access Control Report

# Face Professional Access Control System

## Realtime 1100 mini

with WIFI

HIGH SPEED LONG RANGE FACE RECOGNITION



### Specifications

|   |                                    |
|---|------------------------------------|
| <b>Face / Card / PIN capacity</b>       | 1500                               |
| <b>Record capacity</b>                  | 100,000                            |
| <b>Recognition way</b>                  | Face, Card, Password               |
| <b>Accuracy</b>                         | 0.3                                |
| <b>Language</b>                         | English                            |
| <b>Self-checking function</b>           | Yes                                |
| <b>Face FAR/ FRR</b>                    | 0.001/0.1(%)                       |
| <b>Recognition Speed</b>                | 0.3s                               |
| <b>Face intelligent update function</b> | Yes                                |
| <b>Recognition ways</b>                 | 1:1, 1:N                           |
| <b>CPU</b>                              | Quad-core, 1.7G                    |
| <b>OS</b>                               | LINUX                              |
| <b>Camera</b>                           | Dual camera                        |
| <b>IR LED</b>                           | Yes                                |
| <b>LCD</b>                              | 4" inch HD Touch Screen            |
| <b>Infrared approach receiver</b>       | Yes                                |
| <b>Touch screen</b>                     | Yes                                |
| <b>Communication</b>                    | TCP/IP, U-disk, WIFI               |
| <b>Working voltage</b>                  | DC12V - 24V Wide voltage design    |
| <b>Ambient light</b>                    | 0-50000Lux                         |
| <b>Working temperature</b>              | 0 <sup>o</sup> C-40 <sup>o</sup> C |
| <b>Working humidity(RH)</b>             | 20% ~ 80%                          |
| <b>Door sensor(EN-MG)</b>               | Gate magnetic signal input         |
| <b>Alarm</b>                            | Alarm output                       |



Face



TCP/IP



Personal  
Identity Number



Backup  
Battery



RFID Reader



4G  
(External)



USB Disk



Access  
Control



Cloud



WiFi